

RUBBERWORX

REINFORCED PVC WATER SUCTION AND DISCHARGE



This medium-duty water suction and discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. PVC tube reinforced with a synthetic textile braid and orange PVC helix. PVC tube is designed to handle residual chemicals in water transfer applications.

TUBE:	PVC
REINFORCEMENT:	TEXTILE BRAID
COVER:	ORANGE PVC HELIX
TEMPERATURE:	-13°F to 140°F
BRANDING:	PVC SUCTION AND DISCHARGE 100 PSI
PACKAGING SPECIFICATIONS:	100' COILS AND 20' SECTIONS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
1001206-150	1.50	1.95	100	300	3	29	0.47	100'
1001206-200	2.00	2.60	100	300	4	29	0.71	100'
1001206-300	3.00	3.62	100	300	6	29	1.14	20', 100'
1001206-400	4.00	4.80	75	225	7	29	1.75	20', 100'
1001206-500	5.00	6.05	70	210	9	29	3.00	20', 100'
1001206-600	6.00	7.17	70	210	10	29	3.90	20', 100'
1001206-800	8.00	9.34	70	210	16	29	5.56	20', 100'
1001206-1000	10.00	10.86	40	260	25	29	8.68	20', 100'
1001206-1200	12.00	13.90	28	84	45	29	10.30	20', 100'