

# RUBBERWORX

## PVC WATER SUCTION AND DISCHARGE



This light-duty water suction and discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. PVC tube designed to handle residual chemicals in water transfer applications.

<b>TUBE:</b>	PVC
<b>REINFORCEMENT:</b>	WHITE PVC HELIX
<b>COVER:</b>	PVC
<b>TEMPERATURE:</b>	-23°F to 140°F
<b>BRANDING:</b>	PVC SUCTION AND DISCHARGE 100 PSI
<b>PACKAGING SPECIFICATIONS:</b>	100' COILS AND 20' SECTIONS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
1002106-075	0.75	1.02	100	300	2	29	0.21	20', 100'
1002106-100	1.00	1.29	100	300	3	29	0.29	20', 100'
1002106-125	1.25	1.56	90	270	4	29	0.38	20', 100'
1002106-150	1.50	1.84	90	270	4	29	0.49	20', 100'
1002106-200	2.00	2.39	70	210	5	29	0.72	20', 100'
1002106-250	2.50	2.92	65	195	7	29	0.99	20', 100'
1002106-300	3.00	3.46	55	165	8	29	1.29	20', 100'
1002106-400	4.00	4.56	50	150	12	29	2.05	20', 100'
1002106-500	5.00	5.65	45	135	20	29	3.01	20', 100'
1002106-600	6.00	6.80	45	135	23	29	4.45	20', 100'
1002106-800	8.00	8.95	40	120	34	29	6.86	20', 100'
1002106-1000	10.00	11.34	40	120	40	29	12.05	20', 100'
1002106-1200	12.00	13.19	35	105	50	29	15.27	20', 100'