

RUBBERWORX

RUGGED CHILLER DISCHARGE 150 PSI



This heavy-duty water discharge hose is designed for use with chillers. The rugged construction is designed for repeated use. The EPDM tube and cover are formulated to handle glycol solutions used in chiller applications vs. a SBR commonly found in rubber water discharge hoses.

TUBE:	BLACK EPDM
REINFORCEMENT:	3 PLIES
COVER:	BLACK EPDM
TEMPERATURE:	-25°F to 180°F
BRANDING:	RUGGED CHILLER DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS:	100' COILS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
1011116-200	2.00	2.38	150	450	NA	NA	0.84	100'
1011116-250	2.50	2.90	150	450	NA	NA	0.91	100'
1011116-300	3.00	3.50	150	450	NA	NA	1.12	100'
1011116-400	4.00	4.45	150	450	NA	NA	1.25	100'
1011116-600	6.00	6.50	150	450	NA	NA	3.45	100'
1011116-800	8.00	4.32	150	450	NA	NA	4.55	100'
1011116-1000	10.00	6.50	150	450	NA	NA	6.03	100'