

RUBBERWORX

PETROLEUM TRANSFER 150 PSI



This heavy-duty petroleum suction and discharge hose is designed for use with oils, petroleum based products, and refined fuels. For use in offshore oil transfer, tank truck, oilfield transfer and oil pumping applications. Corrugated cover design for improved flexibility.

TUBE:	BLACK NITRILE BLEND
REINFORCEMENT:	2 PLY TEXTILE AND WIRE HELIX
COVER:	BLACK NITIRILE BLEND
TEMPERATURE:	-22°F to 158°F
BRANDING:	PETROLEUM TRANSFER 150 PSI
PACKAGING SPECIFICATIONS:	100', 200' COILS AND 20' SECTIONS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
2001103-150	1.50	1.93	150	450	7	29	0.79	100'
2001103-200	2.00	2.48	150	450	10	29	1.11	20', 100', 200'
2001103-250	2.50	3.03	150	450	12	29	1.43	20', 100', 200'
2001103-300	3.00	3.50	150	450	15	29	1.89	20', 100', 200'
2001103-400	4.00	4.61	150	450	18	29	2.73	20', 100', 200'
2001103-500	5.00	5.70	150	450	26	29	4.17	20', 100'
2001103-600	6.00	6.69	150	450	30	29	5.29	20', 100'
2001103-800	8.00	8.98	150	450	30	29	9.69	20', 100'