

RUBBERWORX

500 PSI WIRE AIR BRAID



This heavy duty wire reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications. The ozone and abrasion resistant cover holds up to the toughest applications.

TUBE:	BLACK NITIRLE
REINFORCEMENT:	2 HIGH TENSILE STEEL BRAIDED WIRES
COVER:	YELLOW OZONE RESISTANT NITRILE
TEMPERATURE:	-25°F to 180°F
BRANDING:	500 PSI WIRE AIR BRAID
PACKAGING SPECIFICATIONS:	50', 100' COILS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
5002103-075	0.75	1.11	500	2000	6	NA	0.41	50', 100'
5002103-100	1.00	1.45	500	2000	8	NA	0.66	50', 100'
5002103-125	1.25	1.75	500	2000	10	NA	0.86	50', 100'
5002103-150	1.50	2.00	500	2000	12	NA	1.00	50', 100'
5002103-200	2.00	2.50	500	2000	15	NA	1.39	50', 100'
5002103-250	2.50	3.14	500	2000	30	NA	2.15	50', 100'
5002103-300	3.00	3.70	500	2000	35	NA	2.77	50', 100'