

RUBBERWORX

600 PSI WIRE AIR BRAID



This heavy duty wire reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications. The ozone and abrasion resistant cover holds up to the toughest applications

| | |
|----------------------------------|---|
| TUBE: | SYNTHETIC NBR |
| REINFORCEMENT: | 2 HIGH TENSILE STEEL BRAIDED WIRES |
| COVER: | YELLOW OZONE RESISTANT SYNTHETIC RUBBER |
| TEMPERATURE: | -22°F to 180°F |
| BRANDING: | 600 PSI WIRE AIR BRAID |
| PACKAGING SPECIFICATIONS: | 50', 100' COILS |

| SA # | ID (IN) | OD (IN) | WP (PSI) | BURST (PSI) | BEND RADIUS (IN) | VACUUM RATING (HG) | WEIGHT | PACKAGING |
|-------------|---------|---------|----------|-------------|------------------|--------------------|--------|-----------|
| 5002103-050 | 0.50 | 0.80 | 600 | 2400 | 4 | NA | 0.44 | 50', 100' |
| 5002103-075 | 0.75 | 1.10 | 600 | 2400 | 6 | NA | 0.75 | 50', 100' |
| 5002103-100 | 1.00 | 1.45 | 600 | 2400 | 8 | NA | 1.16 | 50', 100' |
| 5002103-125 | 1.25 | 1.80 | 600 | 2400 | 10 | NA | 1.40 | 50', 100' |
| 5002103-150 | 1.50 | 2.00 | 600 | 2400 | 12 | NA | 1.57 | 50', 100' |
| 5002103-200 | 2.00 | 2.50 | 600 | 2400 | 15 | NA | 1.95 | 50', 100' |
| 5002103-250 | 2.50 | 3.05 | 600 | 2400 | 22 | NA | 2.65 | 50', 100' |
| 5002103-300 | 3.00 | 3.70 | 600 | 2400 | 35 | NA | 3.95 | 50', 100' |
| 5002103-400 | 4.00 | 5.00 | 600 | 2400 | 45 | NA | 5.95 | 50', 100' |
| 5002103-600 | 6.00 | 6.95 | 600 | 2400 | 75 | NA | 8.35 | 50', 100' |