

RUBBERWORX

600 PSI WIRE AIR BRAID HIGH TEMP



This heavy duty high temp wire reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications. Specially formulated CPE tube and cover provide the highest temperature ratings for hot compressed air. The ozone and abrasion resistant cover holds up to the toughest applications.

| | |
|----------------------------------|------------------------------------|
| TUBE: | HIGH TEMP CPE |
| REINFORCEMENT: | 2 HIGH TENSILE STEEL BRAIDED WIRES |
| COVER: | YELLOW OZONE RESISTANT CPE |
| TEMPERATURE: | -40°F to 300°F |
| BRANDING: | 600 PSI WIRE AIR BRAID |
| PACKAGING SPECIFICATIONS: | 50' COILS |

| SA # | ID (IN) | OD (IN) | WP (PSI) | BURST (PSI) | BEND RADIUS (IN) | VACUUM RATING (HG) | WEIGHT | PACKAGING |
|-------------|---------|---------|----------|-------------|------------------|--------------------|--------|-----------|
| 5003103-150 | 1.50 | 2.02 | 600 | 2400 | 12 | NA | 1.13 | 50', 100' |
| 5003103-200 | 2.00 | 2.62 | 600 | 2400 | 15 | NA | 1.51 | 50', 100' |
| 5003103-250 | 2.50 | 3.12 | 600 | 2400 | 18 | NA | 1.89 | 50', 100' |
| 5003103-300 | 3.00 | 3.64 | 600 | 2400 | 20 | NA | 2.46 | 50', 100' |
| 5003103-400 | 4.00 | 4.79 | 600 | 2400 | 25 | NA | 4.10 | 50', 100' |