

RUBBERWORX

OILFIELD SUCTION AND DISCHARGE



This heavy-duty oilfield suction and discharge hose is designed for use with unrefined oils, drilling mud, well water, sewage, salt water, and refined fuels. For use in oilfield service for tank trucks, oilfield transfer and pumping applications. Corrugated cover design for improved flexibility.

TUBE:	BLACK SBR BLEND
REINFORCEMENT:	2 PLY TEXTILE AND WIRE HELIX
COVER:	BLACK SBR BLEND
TEMPERATURE:	-22°F to 180°F
BRANDING:	OILFIELD SUCTION AND DISCHARGE 150 PSI
PACKAGING SPECIFICATIONS:	100', 200' COILS AND 20' SECTIONS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
6002203-200	2.00	2.45	150	450	6	29	1.75	20', 100', 200'
6002203-250	2.50	3.05	150	450	8	29	1.80	20', 100', 200'
6002203-300	3.00	3.50	150	450	9	29	1.90	20', 100', 200'
6002203-400	4.00	4.55	150	450	12	29	2.80	20', 100', 200'
6002203-600	6.00	6.60	150	450	25	29	5.65	20', 100'
6002203-800	8.00	8.80	150	450	47	29	7.10	20', 100'