

RUBBERWORX

OIL SUCTION AND DISCHARGE



This heavy-duty oil suction and discharge hose is designed for use with oils, drilling mud, well water, sewage, salt water, and low aromatic content petroleum products. For use in application with tank trucks, oil transfer and pumping applications.

- TUBE:** BLACK SBR BLEND
- REINFORCEMENT:** 2 PLY TEXTILE AND WIRE HELIX
- COVER:** BLACK SBR BLEND
- TEMPERATURE:** -22°F to 180°F
- BRANDING:** OIL SUCTION AND DISCHARGE 150 PSI
- PACKAGING SPECIFICATIONS:** 100', 200' COILS AND 20' SECTIONS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
6003103-200	2.00	2.50	150	450	4	29	1.75	20', 100', 200'
6003103-300	3.00	3.50	150	450	6	29	1.90	20', 100', 200'
6003103-400	4.00	4.60	150	450	10	29	2.80	20'
6003103-600	6.00	6.70	150	450	16	29	5.65	20'
6003103-800	8.00	8.98	150	450	30	29	9.69	20'